


## SOT-323 Plastic-Encapsulate Transistors

### FEATURES

- Ideally suited for automatic insertion
- For Switching and AF Amplifier Applications



### MAXIMUM RATINGS (T<sub>a</sub>=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V <sub>CB0</sub>	Collector-Base Voltage		
	BC856W	-80	V
	BC857W	-50	
	BC858W	-30	
V <sub>CEO</sub>	Collector-Emitter Voltage		
	BC856W	-65	V
	BC857W	-45	
	BC858W	-30	
V <sub>EBO</sub>	Emitter-Base Voltage	-5	V
I <sub>c</sub>	Collector Current –Continuous	-0.1	A
P <sub>C*</sub>	Collector Power Dissipation	150	mW
R <sub>θJA</sub>	Thermal Resistance From Junction To Ambient	833	°C/W
T <sub>J</sub> , T <sub>stg</sub>	Operation Junction and Storage Temperature Range	-55~+150	°C







### DEVICE MARKING



BC856AW=3A; BC856BW=3B;  
BC857AW=3E; BC857BW=3F; BC857CW=3G;  
BC858AW=3J; BC858BW=3K; BC858CW=3L

**ELECTRICAL CHARACTERISTICS (T<sub>a</sub>=25°C unless otherwise specified)**

Parameter	Symbol	Test conditions	Min	Max	Unit
Collector-base breakdown voltage	BC856W BC857W BC858W	$V_{CBO}$	$I_C = -10\mu A, I_E = 0$	-80 -50 -30	V
Collector-emitter breakdown voltage	BC856W BC857W BC858W	$V_{CEO}$	$I_C = -10mA, I_B = 0$	-65 -45 -30	V
Emitter-base breakdown voltage		$V_{EBO}$	$I_E = -1\mu A, I_C = 0$	-5	V
Collector cut-off current		$I_{CBO}$	$V_{CB} = -30V, I_E = 0$		-15 nA
DC current gain	BC856AW, 857AW, 858AW BC856BW, 857BW, 858BW BC857CW, BC858CW	$h_{FE}$	$V_{CE} = -5V, I_C = -2mA$	125 220 420	250 475 800
Collector-emitter saturation voltage		$V_{CE(sat)}$	$I_C = -100mA, I_B = -5mA$		-0.65 V
Base-emitter saturation voltage		$V_{BE(sat)}$	$I_C = -100mA, I_B = -5mA$		-1.1 V
Transition frequency		$f_T$	$V_{CE} = -5V, I_C = -10mA$ $f = 100MHz$	100	MHz
Collector capacitance		$C_{ob}$	$V_{CB} = -10V, f = 1MHz$		4.5 pF


### Typical Characteristics





Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
$\theta$	0°	8°	0°	8°

### SOT-323 Suggested Pad Layout



- Note:
1. Controlling dimension: in millimeters.
  2. General tolerance:  $\pm 0.05$  mm.
  3. The pad layout is for reference purposes only.