

**Features**


- $I_{F(AV)}$  2.0A
- $V_{RRM}$  50V-1000V
- High surge current capability
- Glass passivated chip

**Applications**

- General purpose 1 phase Bridge rectifier applications

**Marking**

- DB20X  
X : From 01 To 7



**Limiting Values (Absolute Maximum Rating)**

Item	Symbol	Unit	Conditions	DB2						
				01	02	03	04	05	06	07
Repetitive Peak Reverse Voltage	$V_{RRM}$	V		50	100	200	400	600	800	1000
Maximum RMS Voltage	$V_{RMS}$	V		35	70	140	280	420	560	700
Average Rectified Output Current	$I_o$	A	60Hz sine wave, R-load, $T_a=25^\circ C$	2.0						
Surge(Non-repetitive) Forward Current	$I_{FSM}$	A	60Hz half sine wave, 1 cycle, $T_j=25^\circ C$	60						
Current Squared Time	$I^2t$	$A^2S$	$1ms \leq t < 8.3ms$ $T_j=25^\circ C$ , Rating of per diode	15						
Operation Junction and Storage Temperature Range	$T_j, T_{stg}$	$^\circ C$		-55 ~ +150						

**Electrical Characteristics** ( $T_a=25^\circ C$  Unless otherwise specified)

Item	Symbol	Unit	Test Condition	Max
Peak Forward Voltage	$V_{FM}$	V	$I_{FM}=2.0A$ , Pulse measurement, Rating of per diode	1.1
Peak Reverse Current	$I_{RRM}$	$\mu A$	$V_{RM}=V_{RRM}$ , Pulse measurement, Rating of per diode	10
Thermal Resistance	$R_{\theta J-A}$	$^\circ C/W$	Between junction and ambient, On glass-epoxi substrate	68
	$R_{\theta J-L}$		Between junction and lead	15

### Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3: TYPICAL FORWARD CHARACTERISTICS






FIG.4: TYPICAL REVERSE CHARACTERISTICS





Dimensions in inches and (millimeters)